DESSO Textile floor covering - Tiles

Arcade

Specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/8 “					
Aspect	ISO 2424		Cut pile					
Dye method			Piece dyed continuous					
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68” x 19,68” (16 tiles per box)					
Primary backing	ISO 2424		Polyester fleece					
Secondary backing	ISO 2424		DESSO ProBase Polyver® - Polyscan®					
Pile fibre composition	ISO 2424		BCF Polyamide 6.6					
Total thickness	ISO 1765	mm	9.5	inch	0.4			
Effective pile thickness	ISO 1766	mm	7.0	inch	0.28			
Total mass	ISO 8543	g/m²	4900	oz/yd²	144.6			
Total pile mass	ISO 2424	g/m²	1540	oz/yd²	45.5			
Effective pile mass	ISO 8543	g/m²	1200	oz/yd²	35.4			
Pile density	ISO 8543	g/cm³	0.171	lb/in³	0.0062			
Number of tufts	ISO 1763	/dm²	1070	/yd²	89463			
Stroll test	ISO 6356	kV	≤ 2,0					
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10⁹					
Horizontal resistance	ISO 10965	Ohm	-					
Use classification	EN 1307		32 Commercial - general use					
Luxury rating	EN 1307		LC 5					
Dimensional stability	EN 986	%	≤ 0,2					
Impact sound reduction ΔL_w	ISO 10140	dB	28					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α_s	0.01	0.05	0.10	0.30	0.50	0.70
Noise reduction	ISO 354	α_w	0.20					
Thermal resistance	ISO 8302	m².K/W	0.101					
Flammability	EN 13501-1		Cfl - s1 (loose laid tested)					
Prodis - GUT	www.pro-dis.info		F7DA50EA					

CE
EN 14041
0493-CPR-0002

Manufactured by:
Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk

Cfl-s1 DS

Quality- and Environmental Management System Certification ISO 9001 & ISO 14001

Tarkett's flooring products are to be installed in full accordance with DESSO installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. Tarkett's flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20190808

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk

Tarkett