DESSO Textile floor covering - Tiles

Neo Core

Specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10 “						
Aspect	ISO 2424		Loop pile						
Dye method			Solution dyed						
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68” x 19,68” (20 tiles per box)						
Primary backing	ISO 2424		Polyester fleece						
Secondary backing	ISO 2424		DESSO ProBase Polyver® - Polyscan®						
Pile fibre composition	ISO 2424		BCF Polyamide 6 and ECONYL® (ECONYL® is made from 100% regenerated content) **						
Total thickness	ISO 1765	mm	5.5	inch	0.2				
Effective pile thickness	ISO 1766	mm	3.0	inch	0.12				
Total mass	ISO 8543	g/m²	4150	oz/yd²	122.5				
Total pile mass	ISO 2424	g/m²	710	oz/yd²	21.0				
Effective pile mass	ISO 8543	g/m²	525	oz/yd²	15.5				
Pile density	ISO 8543	g/cm³	0.175	lb/in³	0.0063				
Number of tufts	ISO 1763	/dm²	1540	/yd²	128759				
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10^9						
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 2						
Dimensional stability	EN 986	%	≤ 0,2						
Impact sound reduction ΔL_w	ISO 10140	dB	24						
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000	
		α_s	0.01	0.02	0.06	0.18	0.29	0.34	
Noise reduction	ISO 354	α_w	0.15						
Thermal resistance	ISO 8302	m².K/W	0.039						
Flammability	EN 13501-1		Bfl - s1 (loose laid tested)						
Prodis - GUT	www.pro-dis.info		AB317551						

CE
EN 14041
0493-CPR-0002

Manufactured by:
Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk

Bfl-s1 DS

ECONYL® ENDLESS POSSIBILITIES

Quality- and Environmental Management System Certification ISO 9001 & ISO 14001

cradle to cradle BRONZE

** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

Tarkett’s flooring products are to be installed in full accordance with DESSO installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. Tarkett’s flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20190808

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk

Tarkett