## Recharge EcoBase

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424	Tufted 1/10 "							
Aspect	ISO 2424	Structured loop pile							
Dye method			Solution	dyed					
Dimension	EN ISO 24342	cm x cm	50 x 50 /	50 x 50 / 19,68" x 19,68" (20 tiles per box)					
Primary backing	ISO 2424		Polyester fleece						
Secondary backing	ISO 2424		EcoBase - 100% recyclable, contains on average 80% positively defined recycled content.*						
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) $^{\ast\ast}$						
Total thickness	ISO 1765	mm	6.5		inch	0.3			
Effective pile thickness	ISO 1766	mm	2.8		inch	0.11			
Total mass	ISO 8543	g/m²	4050		oz/yd²	119.5			
Total pile mass	ISO 2424	g/m²	600		oz/yd²	17.7			
Effective pile mass	ISO 8543	g/m²	345		oz/yd²	10.2			
Pile density	ISO 8543	g/cm³	0.123		lb/in³	0.0044			
Number of tufts	ISO 1763	/dm²	1580		/yd²	132104			
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	≤ 1 x 10	9					
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 1						
Dimensional stability	EN 986	%	≤ 0,2						
Impact sound reduction $\Delta L_w$	ISO 10140	dB	23						
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000	
		α <sub>s</sub>	0.01	0.04	0.06	0.15	0.28	0.31	
Noise reduction	ISO 354	α <sub>w</sub>	0.15						
Thermal resistance	ISO 8302	m².K/W	0.074						
Flammability	EN 13501-1	Bfl - s1 (loose laid tested)							
Prodis - GUT	www.pro-dis.info	www.pro-dis.info		DA					





\* DESSO EcoBase<sup>®</sup> is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle<sup>®</sup> assessment criteria. As described in Cradle to Cradle<sup>®</sup> Certified CM Product Standard Version 3.1. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com For products with acoustic backing: SoundMaster/SoundMaster Lite backings contain 80% recycled polyester felt, SoundMaster Thrive is a low antimony polyester felt.

\*\* ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20230127

Tarkett BV Taxandriaweg 15 NL-5142 PA Waalwijk

